

**Compact Wheel Loader LGL16F-II**

Engine	
Model	Cummins B3.3-C80(UK)
Type	In-line, water cooled, direct injection
Rated power	60Kw
Rated speed	2200rpm
Main Technical Specification	
Rated load	1600kg
Operating weight	5600kg
Rated bucket capacity	0.9m ³
Max.breakout force	52KN
Max.dump clearance	2460mm
Dump reach	905mm
Min. turning radius	4830mm
Lifting time of bucket	≤5s
Total cycling time	≤10s
Tyre size	16/70-20
Transmission System	
Torque Converter	
Type	Single stage(Shantui)
Cooling type	Pressure oil circulating
Gear box	
Type	Power shift(Shantui)
Gear shifts (Forward/Reverse)	F2/R2
Traveling speed(Km/h)	
Forward/Reverse I	6/6
Forward/Reverse II	24/24
Dimensions	
Length(with bucket on ground)	5500mm

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

website: www.shlongji.com

[Wheel Loader](#), [Road Roller](#), [Dump Truck](#)

Width(to outside of wheels)	1960mm
Height(To the top of the cab)	2800mm
Wheel base	2200mm
Tread	1496mm

Shanghai Longji Construction Machinery Co., Ltd.
Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100
Tel: +86-21-541-71571
website: www.shlongji.com

E-mail: info@shlongji.com
Fax: +86-21-541-71572
[Wheel Loader](#), [Road Roller](#), [Dump Truck](#)